

PRODUCT DATA SHEET

Sika® Antifreeze 1% LB

COLD WEATHER CONCRETING ADMIXTURE

DESCRIPTION

A safe economical admixture in liquid form to produce high quality concrete at moderately low temperatures.

USES

Sika® Antifreeze 1% LB is ready for use in cold conditions such as:

- Slight daytime frost
- Expected overnight frost
- Expected cold periods
- when under normal conditions work would have to stop

CHARACTERISTICS / ADVANTAGES

Sika® Antifreeze 1% provides the following properties:

- Improves workability without increased water
- Reduction in water without loss of workability
- Increased frost resistance
- Improved strengths
- Chloride free-does not attack reinforcement

PRODUCT INFORMATION

Composition	Special salts
Packaging	20 kg Jerry can
Appearance / Colour	Transparent
Shelf life	18 months from date of production if stored properly in original unopened packing.
Storage conditions	Not affected by frost down to -12°C.
Density	1.01 ± 0.01 kg/l

TECHNICAL INFORMATION

Specific Advice

When concreting in cold conditions, attention should be paid to the following important points:

- Keep form work and reinforcement free from water, snow or ice. Where required pre-heat to 0°C min., all form work must be designed to act as thermal insulation.
- Maintain minimum temperature of concrete at 5°C.
- Protect against loss of moisture and heat by maintaining cover and insulation.
- If Sika® Antifreeze 1% LB freezes in the drum, thaw gradually in a heated environment (Avoid direct flame contact). Once thawed all properties remain unaffected.

APPLICATION INFORMATION

Recommended Dosage	1% by weight of cement.
Dispensing	Sika® Antifreeze 1% LB is added to the mixing water prior to its addition to the aggregates.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Near East
Secteur 5 Rue 70
Jisr el Bacha Beirut
Tel: +961 1 510270
lbn.sika.com

PRODUCT DATA SHEET
Sika® Antifreeze 1% LB
September 2020, Version 01.0

SikaAntifreeze1%LB-en-(10-2020)-
1.pdf

BUILDING TRUST

